



چراغ‌های ضد نم و غبار مدل هرکولد

چراغ ضد نم و غبار هرکولد با طراحی پیشرفته مازی‌نور با لنزهای هدفمند برای پخش نور متنوع برای محیط صنعتی طراحی شده است. ساختار محکم و بادوام و درجه حفاظت (IP66) از ویژگی‌های این چراغ است.

HERCULED Dust & Moisture Proof High/Low Bay Luminaire

HERCULED dust & moisture proof high/low bay luminaire is Mazinoor state of the art design suitable for surface mount or suspending in industrial area with specially designed lenses to deliver a variety of light distributions. Sturdy body and high ingress protection (IP66) are among the highlights of this luminaire.

HERCULED Dust & Moisture Proof High/Low bay Luminaires

Application

Suitable for high/low bay dusty industrial applications where durability, high efficacy, high ingress protection (IP66), and directed light distribution are required.

Technical Data

Body:

- Gray or milk white powder coated sturdy high pressure die-cast aluminum body
- Dacromet coated exterior screws and galvanized interior screws
- Sturdy steel handle with dacromet coated screws and graduated 5-degree scales for well controlled angle adjustment and reliable safety
- Thermal and pressure resistant silicon gasket
- Ingress protection: IP66

Optics:


- Narrow, medium, or wide light distribution with clear polycarbonate lenses with 95% efficacy
- 5-mm flat clear tempered glass diffuser

Electrical components:

- High efficacy LED modules
- Lumen Maintenance (L80) > 100,000hrs
- Color temperatures: 4000K or 5000K
- High quality constant current LED driver (PF > 0.9)
- PVC solid wire
- Polyamide cable gland
- Looping capability

Ordering Options:

- Gray or milk white powder coated aluminum body cover (upon request)
- Nano coated clear glass diffuser (upon request)



		Flicker Free		RAL 9002	RAL 7043	LED	IK 08	IP 66		LOOPING
وزن (کیلوگرم)	رنگ نور (کلوین)	بازدهی چراغ (لومن بر وات)	شار نوری چراغ (لومن)	توان چراغ (وات)	مدل					
8.5	4000	150	36000	240	M312NLED10740-S					
8.5	5000	150	36000	240	M312NLED10750-S					
8.5	4000	150	36000	240	M312MLED10740-S					
8.5	5000	150	36000	240	M312MLED10750-S					
8.5	4000	150	36000	240	M312WLED10740-S					
8.5	5000	150	36000	240	M312WLED10750-S					




► آویختن چراغ با استفاده از یک یا دو قلاب آویز
Suspension of the luminaire with one or
◀ two provided suspension brackets



• این مدل چراغ‌ها به رنگ شیری نیز عرضه می‌شود. (M312...-W)

• Available also in gray white powder coated finishing. (M312...-W)

چراغ‌های ضد نم و غبار مدل هرکولد



		Flicker Free		RAL 9002	RAL 7043	LED	IK 08	IP 66		LOOPING
وزن (کیلوگرم)	رنگ نور (کلوین)	بازدهی چراغ (لومن بر وات)	شار نوری چراغ (لومن)	توان چراغ (وات)	مدل					
8.5	4000	160	32000	200	M312NLED9740-S					
8.5	5000	160	32000	200	M312NLED9750-S					
8.5	4000	160	32000	200	M312MLED9740-S					
8.5	5000	160	32000	200	M312MLED9750-S					
8.5	4000	160	32000	200	M312WLED9740-S					
8.5	5000	160	32000	200	M312WLED9750-S					

• Available also in gray white powder coated finishing. (M312...-W)

• این مدل چراغ‌ها به رنگ شیری نیز عرضه می‌شود. (M312...-W)

Application

Suitable for high/low bay dusty industrial applications where durability, high efficacy, high ingress protection (IP66), and directed light distribution are required.

Technical Data

Body:

- Gray or milk white powder coated sturdy high pressure die-cast aluminum body
- Dacromet coated exterior screws and galvanized interior screws
- Sturdy steel handle with dacromet coated screws and graduated 5-degree scales for well controlled angle adjustment and reliable safety
- Thermal and pressure resistant silicon gasket
- Ingress protection: IP66

Optics:

- Narrow, medium, or wide light distribution with clear polycarbonate lenses with 95% efficacy
- 5-mm flat clear tempered glass diffuser

Electrical components:

- High efficacy LED modules
- Lumen Maintenance (L70) > 100,000hrs (at 60°C ambient temperature, in M312HT... model)
- Color temperatures: 4000K or 5000K
- High quality constant current LED driver (PF > 0.9)
- PVC solid wire
- Polyamide cable gland
- Looping capability

Ordering Options:


- Gray or milk white powder coated aluminum body cover (upon request)
- Nano coated clear glass diffuser (upon request)







► آویختن چراغ با استفاده از یک یا دو قلاب آویز
Suspension of the luminaire with one or
◀ two provided suspension brackets



چراغ‌های ضد نم و غبار مدل هرکولد HT HERCULED HT Dust & Moisture Proof High/Low bay Luminaires



								
								
وزن (کیلوگرم)	رنگ نور (کلوین)	بازدهی چراغ (لومن بر وات)	شار نوری چراغ (لومن)	توان چراغ (وات)	مدل			
8.4	4000	159	27000	170	M312HTNLED8740-S			
8.4	5000	159	27000	170	M312HTNLED8750-S			
8.4	4000	159	27000	170	M312HTMLED8740-S			
8.4	5000	159	27000	170	M312HTMLED8750-S			
8.4	4000	165	28000	170	M312HTWLED8740-S			
8.4	5000	165	28000	170	M312HTWLED8750-S			

سفارشات خاص:

- امکان استفاده از درپوش بدنه آلومینیوم با پوشش رنگ پودری الکترواستاتیک طوسی یا شیری بنا به سفارش
- دیفیوزر شیشه‌ای شفاف با پوشش نانو بنا به سفارش