





چراغ پروژکتوری ساترن

چراغ پروژکتوری ساترن با طراحی پیشرفته مازی نور برای روشنایی فضاهای آزاد و کاربری‌های پروژکتوری طراحی شده است. ساختار محکم، بادوام و درجه حفاظت (IP66) از ویژگی‌های این چراغ است.

SATURN Floodlight

SATURN floodlight is Mazinoor state of the art design suitable for floodlight applications. High pressure die-cast aluminum body and high ingress protection (IP66) are among the highlights of this luminaire.

SATURN FloodLight

Application

Suitable for outdoor and floodlight applications where aesthetics, durability, and directed or uniform light distribution are required.

Technical Data

Body:


- Gray powder coated sturdy high pressure die-cast aluminum body
- Dacromet coated exterior screws and galvanized interior screws
- Sturdy steel handle with dacromet coated screws and graduated 5-degree scales for well controlled angle adjustment and reliable safety
- Thermal and pressure resistant silicon gasket
- Ingress protection: IP66



Optics:

- Symmetrical narrow or wide light distribution with clear polycarbonate lenses with 95% efficacy
- 5-mm flat clear tempered glass diffuser

Electrical components:

- High efficacy LED modules
- Lumen Maintenance (L80) > 100,000hrs
- CRI > 70
- Color temperatures: 3000K, 4000K, or 5000K
- High quality constant current LED driver (PF > 0.9)
- PVC solid wire
- Polyamide socket and plug
- Polyamide cable gland
- Looping capability



		RAL 7043		LED	IP66		Looping
							
وزن (کیلوگرم)	دمای رنگ نور (کلوین)	بازدهی چراغ (لومن بر وات)	شار نوری چراغ (لومن)	توان چراغ (وات)	مدل		
9.2	3000	142	34000	240	M313NLED10730-S		
9.2	4000	150	36000	240	M313NLED10740-S		
9.2	5000	150	36000	240	M313NLED10750-S		
9.2	3000	142	34000	240	M313WLED10730-S		
9.2	4000	150	36000	240	M313WLED10740-S		
9.2	5000	150	36000	240	M313WLED10750-S		